



Structure: Best in Class!

- · Fully boxed aluminum frame
- Lightweight, unibody design
- · Assembled with aircraftgrade inserts and trusshead screws
- · Each non-marring caster has a lock and is rated for 900 lbs
- Total cart rated for 1500 lbs
- Swivel locks on one end



Enclosure: Best in Class!

- Healthcare approved, durable and easy to clean
- · Last 5x longer than woven enclosures
- · Available in white or translucent
- · Antimicrobial, non-woven. anti-static and fire-resistant
- Two pass-thru slips for passing cable, conduit or tools
- dust between moves
- · Quick installation for change-out or replacement

Lenexa, Kansas



Interior Lighting: **Best in Class!**

- · Dimmable HALO LED lighting system illuminates work area
- · LED shelf illuminates lower enclosure



Filtration: Best in Class!

- · Lab-tested design
- HEPA 99.99+% at 0.3 μm
- · Individually tested AND certified with testing results
- · MERV 8 Pleated Pre-filter
- 99.99% HEPA exceeds ASHRAE 52.2 MERV 16 Rating
- · Fan rated at 750 CFM
- Airflow: 500+ CFM at exhaust
- Variable speed control allows for precise airflow control to meet the needs of your job
- · HEPA filter mounted after fan for best in class particle reduction



Advanced Safety Features

- Red IN USE light
- Differential pressure gauge / manometer
- · Walk-off mat storage tacky mat compartment



Premium Door Package


- Large window
- · Lock and key set
- · Work permit slip holder



Electrical: Best in Class!

- Negative air machine conforms to UL Standard 507 and Certified to CSA STD 22.2 No. 113
- GFCI protected outlets located inside the unit for convenience
- · 25 ft. retractable cord
- · Three-way electrical switch wired for 120 vac for US
- · Enhanced infectionprevention capability with both external & internal on/ off switches for negative air machine





913.789.9590

info@hepacart.com



HEPACART Classic Mobile Containment System

Manually Adjusted, Spring-Loaded, Telescoping Poles Offer Maximum Flexibility

Capacity: 1 Plus Tools and Ladder



55 **CLASSIC**

MODEL#: HC55U18.ETL

Working Dimensions 60" L x 29"W Raises 10 ft. 6 in. (Up to 14 ft, with additional options) Working Weight: 350 lbs Fits through any standard 36" door.





Capacity: 2 Plus Tools

CLASSIC

MODEL#: HC74U18 FTI

Working Dimensions 80" L x 29"W Raises 10 ft. 6 in. (Up to 14 ft. with additional options) Working Weight: 375 lbs Fits through any standard 36" door.



Capacity: 2 Plus Tools and Ladder For Large Projects



CLASSIC

MODEL#: HC74UX18.ETL

Working Dimensions 80" L x 39"W Raises 10 ft. 6 in. (Up to 14 ft. with additional options) Working Weight: 400 lbs Fits through any standard 42" door.



HEPACART® CLASSIC FEATURES

Most Versatile Raise/Lower System

- · Telescoping, springloaded extension for tight seal
- Ready to move in seconds
- Raises up to 10' 6" height
- · Individual articulation at all four corners adjusts to nearly any ceiling
- · No tools required
- Add optional tall enclosure to reach 12 ft. ceilings
- Add optional Multiple Tile Adapter to Tall Enclosure, to reach 14 ft. ceilings

Exclusive: Top Slide-out

- Offsets top frame up to 8" at the ceiling
- · Ideal for working around wall obstacles like handrails, art, nurse's stations, etc.
- · Locks into place









Auto-Lift Mobile Containment System

Push Button Auto-Lift with Dual Actuators Provides Unparalleled Ease of Use

Capacity: 1 Plus Tools and Ladder



AUTO-LIFT

MODEL#: HC55U1821A.ETL

Working Dimensions 60" L x 29"W Extends 10 ft. 6 in. (Up to 14 ft. with additional options) Working Weight: 350 lbs Fits through any standard 36" door.



Capacity: 2 Plus Tools and Ladder



MODEL#: HC74U1821A.ETL

Working Dimensions 80" L x 29"W Extends 10 ft. 6 in. (Up to 14 ft. with additional options) Working Weight: 375 lbs Fits through any standard 36" door.



Capacity: 2 Plus Tools and Ladder For Large Projects



AUTO-LIFT

MODEL#: HC74UX1821A.ETL

Working Dimensions 80" L x 39"W Extends 10 ft. 6 in. (Up to 14 ft. with additional options) Working Weight: 400 lbs Fits through any standard 42" door.



HEPACART® AUTO-LIFT FEATURES



Exclusive: Easiest Raise /Lower System

- · Two internal actuators adjust the enclosure individually to the desired height with the push of a button
- Allows for angle adjustment up to 45° for ceilings and floors
- · Easy-to-replace actuators with stationary motors

- · Replaces the Classic mechanical operation extension poles
- Each actuator rated for 200 lbs
- No tools required







HEPACART Additional Unit Specifications

Recommended Ladders

- 6 ft. 8 ft. and 10 ft shelf ladders
 - · 6 ft A-frame ladder
- · Taller extension ladders with the Adjustable Ladder Extension Module
- A-frame ladders fully open in the HEPACART 74 and 74X models or can rest securely on the built-in ladder shelf on all HEPACART models.

Electrical Specifications


- All electrical components UL listed
 - North American models:
 - 120 volt / 60 Hz—12 amps International models:
 - 230 volt / 50 Hz—8 amps CE

Filtration Specifications

- Lab-tested filtration system with MERV 8 pleated pre-filter and medical grade HEPA 99.99%+ at 0.3 microns
 - Every HEPACART® receives HEPA filter integrity tests (IEST-RP-CC0034.2) and particulate tests for ISO 14644 Class V air.
- Testing and certification paperwork included in each purchase.
- Re-testing recommended annually
- Recertification testing service available from HEPACART

HEPA-Filter: 24 in x 24 in x 6 in MERV 8 Pre-Filter: 24 in x 24 in x 1 in

HEPACART® 55 Classic or Auto-Lift




External Length: 60 in [1524 mm]

Top frame slides 8 in [203.2 mm] to work around wall obstacles (Classic Only)

> Encloses one 2 ft x 4 ft tile or two 2 ft x 2 ft tiles

Add the multiple tile adapter to access up to two 2 ft x 4 ft tiles

HEPACART® 74 Classic or Auto-Lift



Top frame slides 8 in [203.2 mm] to work around wall obstacles (Classic Only)

Encloses one 2 ft x 4 ft tile or two 2 ft x 2 ft tiles

Add the multiple tile adapter to access up to two 2 ft x 4 ft tiles

HEPACART® 74X Classic or Auto-Lift





Add the multiple tile adapter to access up to three 2 ft x 4 ft tile

Add Multiple Tile Adapter to

reach 12 ft. for Auto-Lift [3657.60 mm]

> 14 ft for Classic [4267.20 mm]

Add

Extra Tall Enclosure to reach 12 ft. Classic Only [3657.6 mm]

Standard Enclosure raised height: 10 ft.6 in. [3251.2 mm]

Lowered Height:

76.5 in. [1943.1 mm]



Reach New M Heights

ADJUSTABLE EXTENSION MODULE | Ladder Height

- Adjustable extension allows longer single section and extension ladder to be used
- Utilize up to a 16 ft. ladder
- Folds into place for transport between moves
- No tools for operation
- Removeable from unit
- Upgrade or retrofit existing model
- Works with many sizes, types and brands of ladders
- Keeps worker inside the perimeter of the cart



ALEM (HC55U and HC74U Series) ALEM74X (HC74UX Series)

Add Total Visibility

VISION PANELS | Side Windows for Complete Visibility

- Two large side windows in the cart when visibility is the paramount concern
- Available as one window with wall access



VPHC55U (HC55U Series) VPHC74U (HC74U Series) VPHC74UX (HC74UX Series)

Add Flexibility and Convenience for Current and Future Projects

Add Wall Access

TOTAL WALL ACCESS / Upgrade or Retrofit for CLASSIC

- Cart: Sliding door opens on the side to provide comfortable wall access between 12" and 60" in height
- Enclosure: Removable windows in the enclosure allows access to the wall area above 72"
- Ideal for wall mounted electrical. Includes two windows and two pass-thrus



Interior View: Upper Wall Window Folds Down.



Exterior View: Open Wall Access Door w/ Foam Protected Flange.



Interior View with Single Vision Panel

PART #: TWA55U18 (HC55U Series) TWA74U18 (HC74U Series) WA74UX18 (HC74UX Series)

Access Multiple Tiles

MULTIPLE TILE ADAPTER | Expanded Access

 Expand to 2x to 3x the workable space in ceiling

Add-ons to Work Efficiently

- Fits in the top frame of the unit
- Maintain minimal footprint on the floor



- Reach up to 14 ft. when used with 12 ft. tall enclosure on a CLASSIC model
- Reach up to 12 ft. when used with an AUTO-LIFT model

PART #:

MTA55HALO (HC55U Series) MTA74HALO (HC74U Series) MTA74XHALO (HC74UX Series)

Convert Cart to Job Box

TWA74UX18 (HC74UX Series) LOCKABLETOP* | Converts CLASSIC HEPACART® or DUSTBUGGY® to Lockable Job Box

- Top swings up from the inside; locks with pins
- Secures items left in the cart

PART#-

LTHC55U (HC55U Series) LTHC74U (HC74U Series)

* not compatible with the Auto Lift or Wall Access options at this time.





No Outlet - No Problem

LITHIUM BATTERY KIT | Includes Fast Charger and Shelf

- Provides power for any HEPACART® product
- Mobile app enabled
- Built in surge-allowances and multi-state protection
- Zero fumes and zero noise
- Back up emergency power



PART # HC-BAT-KIT-GZY1500X



HEPACART Enclosure Options and Replacements

Enclosure Visibility

ENCLOSURE WINDOWS | Added Visibility

- · Two large side windows in the enclosure providing maximum visibility in the contained space
- · Available in White or Translucent



PART#: CW55 (HC55U Series) CW74 (HC74U Series) CW74X (HC74UX Series)

Installed or Replacement

TRANSLUCENT ENCLOSURE

- · Available in standard height reaching up to 10 ft 6 in or as a tall version reaching up to 12 ft
- · Allows light and some visibility inside of the cart.
- · Antimicrobial, flameresistant, odor-resistant, anti-static, durable, stainresistant and no fiber shedding



REPLACE / RETROFIT PART#:

PTC157x64-T18 (Translucent HC55U Series) PTC157x88-T18 (Translucent HC55U Series) -12 ft PTC195x64-T18 (Translucent HC74U Series) PTC195x88-T18 (Translucent HC74U Series) -12 ft PTC215x64-W18 (White HC74UX Series) PTC215x88-T18 (Translucent HC74UXSeries) -12 ft

High Ceilings (12'+)

TALL ANTIMICROBIAL PROTECTED ENCLOSURE For All HEPACART® **CLASSIC Mobile** Containment

- Reaches up to 12 ft.+
- · Antimicrobial, flameresistant, odor-resistant, anti-static, durable, stainresistant and no fiber shedding



PART#:

PTC157x88-W18 (White HC55U Series) -12 ft PTC195x88-W18 (White HC74U Series) -12 ft PTC215x88-W18 (White HC74UX Series) -12 ft

Expanded Access

SLIDE-OUT ENCLOSURE TOP FOR CLASSIC **HEPACART®**

- · Allows the top frame of the enclosure to be extended out up to 8"
- Perfect for working around wall mounted obstacles



- Locks into place when not in use
- Included on Classic HC55U18 and HC74U18 Series models. To retrofit existing units use same part number

PART #: SOCO

Standard Replacements

HEPACART® | DUSTBUGGY™ ANTIMICROBIAL PROTECTED ENCLOSURE FOR REPLACEMENT OR **RETROFIT**

- · Standard 10 ft. 6 in. white enclosure replacement
- Antimicrobial, flame-resistant, odor-resistant, anti-static. durable, stain-resistant and no fiber shedding

REPLACE / RETROFIT PART#: PTC157x64-W18 (White HC55U Series) PTC195x64-W18 (White HC74U Series) PTC215x64-W18 (White HC74UX Series)



Go Even Higher -14 ft +

STACKABLE EXTENSION MODULE FOR HEPACART

- · Each stackable extension adds 2 ft. to the enclosure height
- · Securely fastens to the HEPACART® and to each other
- · For Auto-Lifts carts only

PART #: SEMHC55U18A (HC55U Series) SEMHC74U18A (HC74USeries) SEMHC74UX18A (HC74UX Series)



913.789.9590 Lenexa, Kansas info@hepacart.com



HEPACART Options, Upgrades and Consumables

Monitor Pressure

DIGITAL PRESSURE MONITOR | Advanced

- Configurable to monitor positive or negative pressure in protected spaces
- Complete system with a graphic user interface

PART #: **HCRPM**



Keep it Ready



WALK-OFF MATS

- Measures 18" x 36" / 60 pack
- · Fits into the walk-off mat tray under HEPACART® and DUSTBUGGY® models
- · Includes non-slip frame and mats

PART#: CM

PART#: CMR (Refill mats only)

Recommended Ladder

NEW! Access Floors

FLOOR ACCESS OPTION

- Removable floor plate for access below
- · Protective gasket to the floor
- · 27" x 19" opening
- · Adjustable and removable





PART#: DBFAO74

Available on DUSTBUGGY® only

Replacement Filters

99.99% MEDICAL GRADE HEPA-**FILTER**

- · Manufactured by Camfil-Farr
- · Double gasketed
- 24" x 24" x 6"
- · Lab-testing results were achieved with this HEPA-Filter model

PART#: HF24246

PLEATED PRE-FILTERS

- 24" x 24" x 1"
- · MERV 8 high velocity
- · Case of 12

PART#: PF24241



HEPA VACUUM FOR CLEANING

- · Quiet, powerful 1.25HP motor capable of 67 CFM
- HEPA-tested to meet a minimum efficiency of 99.99% at 0.3 microns

PART#: HVBGD930



CLEAN KIT

- · Convenient storage of recommended cleaning supplies
- Includes cleaner and wipes

PART#: **HCCK**



TOP DUST COVER

· Keeps the cart free from dust while in storage or transport

PART#:

DCHC55 (HC55U Series) DCHC74 (HC74U Series) DCHC74UX (HC74UX Series)



FULL DUST COVER

· Encloses the entire cart keeping it free from dust and scratches while in storage or transport






SHELF LADDERS

 Available in 6 ft., 8 ft. and 10 ft. sizes

PART#:

GBSL201206 (6 ft. ladder) GBSL201208 (8 ft. ladder) GBSL201210 (10 ft. ladder)

· Other ladders sourced on request



Compliance, Air Testing Certifications and Listing Authorities

Certified Lab Results

Independent lab testing conducted by **LMS Technologies, Inc.** — Bloomington, MN USA

Test Type: Single-pass HEPACART®:

Al Vatine, President | John Cherne, Microbiologist




Tests	Up/Down x100
Staph aureus Average	99-997%
MS-2 Average	99-9999%
Aspergillus Average	99.996%

Scope: Perform a viability test on Hepacart® model DAHC55U-H with 3 organisms: Staph aureus ATCC 6538, Aspergillus Niger ATCC 1004, and MS-2 Phage ATCC 15597-B1. Calculate collection efficiency. Method: Testing was performed in a custom manufactured HEPA filtration device. Organisms were grown on appropriate media, harvested and resuspended in saline to 1.0 x 106. Suspensions of organisms were then aerosolized into the Hepacart using a nebulizer for 5 min.

Downstream air was sampled using a SKC biostage impactor calibrated to draw 28 liters/min. The recovered organisms were enumerated after 1-2 days incubation. Testing for each organism was done in triplicate. The filtration efficiency was calculated by formula:

Efficiency = (Upstream-downstream)/Upstream x 100.

Based on this battery of tests, you can be confident that every HEPACART® from the factory is ready to clean the air to the highest ICRA level with 99.99% efficiency or greater at 0.3 microns. The filter integrity tests (IEST-RP-CC0034.2) and particulate tests confirm ISO 14644 compliant Class 5 air.



5 Steps to Air Quality Peace of Mind

#1. LAB-TESTED DESIGN:

The HEPACART® designed system has been tested by third-party labs including LMS Technologies with impressive results.

#2. SMOKE-TESTED FOR PROPER AIRFLOW:

The HEPACART® filtration system design has been smoke-tested to make sure the air is being contained and filtered. The design of air-flow is critical to containment.

#3. FILTER SCAN TESTED AT FACTORY:

The HEPA-filters are first scan-tested at the factory and come with a 99.99% certification — even more efficient than the standard HEPA classification.

#4. EACH UNIT IS INDIVDUALLY TESTED:

Every HEPACART® is tested as an assembled unit with an ATI Photometer, a EBT Balometer and an EBT Micromanometer with an ATI Generator to confirm proper filter installation and integrity.

#5. TESTING EQUIPMENT CALIBRATED ANNUALLY:

All testing equipment is recertified on an annual basis.

When testing is completed and the unit is satisfactory, each HEPACART® is given a Certification of Compliance. A report of all testing results are provided to your company for record keeping and compliance.

The electrical system and sound generation are also tested for each HEPACART®

Re-test the equipment on an annual basis at minimum or whenever it is suspected the HEPA-filtration system has been compromised or damaged.

On-Site Testing and Compliance Services

- Turn-key quoting, scheduling and execution of on-site filter integrity and air-flow testing.
- Recommended annually on all HEPA-filtration mobile units for ICRA compliance.



Domestic Compliance Listing U.S.A.

- · All HEPACART® units
- Testing peformed by Intertek
- Conforms to UL Standard 507
- · Standard U.S. grounded plug
- · 25 ft. cord reel, and GFCI outlets
- 120 vac. / 60 Hz



International Compliance Listing

CANADA

- All HEPACART® units
- Testing peformed by Intertek
- · Certified to CSA STD 22.2 No. 1
- Same specs as US model



UNITED KINGDOM / EUROPE

- All HEPACART® units
- Testing performed by Intertek
- Conforms to CE and UKCA requirements
- Electrical plugs configured to destination country specs
- Equipped with inlet plug in place of cord real

AUSTRALIA / MIDDLE EAST ASIA / SOUTH AMERICA

- All HEPACART® units
- Built to the CE specification
- Electrical plugs configured to destination country



